

A safe and intelligent electric boiler

to maximize comfort and energy savings


- ✓ Power modulation
- ✓ Advanced electronic control
- ✓ Immersion temperature sensor
 - ✓ Ease of installation












Dual Energy Layout



Mechanical features

- Compact unit with wall hung capabilities.
- Distinct control panel separates electrical/controls from the heating section for easier access and improved maintenance. (A)

Electrical features

- High quality electronic control overlooks operational and safety functions. (B)
- The boiler water temperature, measured with an enhanced precision immersion sensor, heating modified in response to outside temperature (sensor supplied).
- Individual status lamp shows the operation of each heating element and the circulator on the control board. (C)
- Heating elements are activated in sequence and randomly through reliable 22 VDC relays. (D)
- Pump relay included.
- High limit temperature control included. (E)
- Approved for line voltage hook-up in copper or aluminum.





Technical specifications

MODELS	HYDRA 09	HYDRA 15	HYDRA 18	HYDRA 20	HYDRA 24	HYDRA 29
Power (kW)	9 kW	15 kW	18 kW	20 kW	24 kW	29 kW
Net output (BTU/h)	30,708	51,180	61,416	68,240	81,888	98,948
FLECTRICAL SUPPLY 120/240-60-1						

Dettson Industries inc. reserves the right to make any changes to the sheet or its products at any time without notice



3400, boulevard Industriel Sherbrooke, Quebec, J1L 1V8 Canada



